

TECHNICAL SPECIFICATION MX-06070 (6 V 7.0 AH)

20 HOURS RATE

I N D E X		S P E C I F I C A T I O N	
NOMINAL VOLTAGE		6 V	
NOMINAL CAPACITY (20HR)		6.00 AH (DISCHARGE TO 5.25 V)	
10 HOUR RATE CAPACITY		5.55 AH (DISCHARGE TO 5.25 V)	
5 HOUR RATE CAPACITY		5.12 AH (DISCHARGE TO 5.25 V)	
1 HOUR RATE CAPACITY		3.60 AH (DISCHARGE TO 5.25 V)	
CAPACITY AFFECTED BY TEMPERATURE		30°C (86°F)	103%
		25°C (77°F)	100%
		10°C (50°F)	90%
		-10°C (14°F)	74%
INTERNAL RESISTANCE		25°C FULL CHARGE	APPROX. LESS THAN 16 mΩ
MAX. DISCHARGE CURRENT		24 A (CONTINUOUS)	
SELF DISCHARGE (20°C, 68°C)		AFTER 1 MONTH	5%
		AFTER 3 MONTH	10%
		AFTER 6 MONTH	19%
WEIGHT		APROX. 1.15 Kg (2.54 lbs)	
WEIGHT EFFICIENCY (20HR)		31.3 WH/Kg	
VOLUME EFFICIENCY (20HR)		71.7 WH/L	
CONSTANT VOLTAGE CHARGE	FLOATING	CHARGING VOLTAGE	6.75 ~ 6.90 V (20°C)
		MAX. CHARGING CURRENT	NO LIMIT
	CYCLE	CHARGING VOLTAGE	7.20 ~ 7.50 V (20°C)
		MAX. CHARGING CURRENT	LESS THAN 2.40 A
BATTERY LIFE	FLOATING	AT 25°C (77°F)	6.5 YEARS
		AT 35°C (95°F)	5 ~ 6 YEARS
	CYCLE	100% DISCHARGE	260 CYCLE
		50% DISCHARGE	600 CYCLE
		30% DISCHARGE	1200 CYCLE
TERMINAL TYPE		A	
BATTERY CONTAINER & COVER MATERIAL		ABS	
BATTERY TYPE		VRLA – TYPE	
DIMENSION (± 1MM)	LENGTH	5.95 INCH / 151 MM	
	WIDTH	1.34 INCH / 34.0 MM	
	HEIGHT	38.4 INCH / 97.5 MM	
	TOTAL HEIGHT	3.84 INCH / 97.5 MM	