

TECHNICAL SPECIFICATION MX-06100 (6 V 10 AH)

20 HOURS RATE

I N D E X		S P E C I F I C A T I O N		
NOMINAL VOLTAGE		6 V		
NOMINAL CAPACITY (20HR)		10.0 AH (DISCHARGE TO 5.25 V)		
10 HOUR RATE CAPACITY		9.30 AH (DISCHARGE TO 5.25 V)		
5 HOUR RATE CAPACITY		8.55 AH (DISCHARGE TO 5.25 V)		
1 HOUR RATE CAPACITY		6.00 AH (DISCHARGE TO 5.25 V)		
CAPACITY AFFECTED BY TEMPERATURE		30°C (86°F)	103%	
		25°C (77°F)	100%	
		10°C (50°F)	90%	
		-10°C (14°F)	74%	
INTERNAL RESISTANCE		25°C FULL CHARGE	APPROX. LESS THAN 9 mΩ	
MAX. DISCHARGE CURRENT		40 A (CONTINUOUS)		
SELF DISCHARGE (20°C, 68°C)		AFTER 1 MONTH	5%	
		AFTER 3 MONTH	10%	
		AFTER 6 MONTH	19%	
WEIGHT		APROX. 2.12 Kg (4.67 lbs)		
WEIGHT EFFICIENCY (20HR)		28.3 WH/Kg		
VOLUME EFFICIENCY (20HR)		83.7 WH/L		
CONSTANT VOLTAGE CHARGE	FLOATING	CHARGING VOLTAGE	6.75 ~ 6.90 V (20°C)	
		MAX. CHARGING CURRENT	NO LIMIT	
	CYCLE	CHARGING VOLTAGE	7.20 ~ 7.50 V (20°C)	
		MAX. CHARGING CURRENT	LESS THAN 4.00 A	
BATTERY LIFE	FLOATING	AT 25°C (77°F)	6.5 YEARS	
		AT 35°C (95°F)	5 ~ 6 YEARS	
	CYCLE	100% DISCHARGE	260 CYCLE	EXPECTED VALUE
		50% DISCHARGE	600 CYCLE	
		30% DISCHARGE	1200 CYCLE	
TERMINAL TYPE		A		
BATTERY CONTAINER & COVER MATERIAL		ABS		
BATTERY TYPE		VRLA – TYPE		
DIMENSION (± 1MM)	LENGTH	5.94 INCH / 151 MM		
	WIDTH	1.97 INCH / 50.0 MM		
	HEIGHT	3.70 INCH / 94.0 MM		
	TOTAL HEIGHT	3.98 INCH / 101.0 MM		